



*Semi-style driveover option*

# Driveover Sprayer TRAILER



*Pull-type driveover option*

<b>Main Frame</b>	16" I Beam, 26 lbs. per foot
<b>Capacity</b>	45,000 lb. GVWR; Split or Non-split Axles
<b>Outriggers</b>	20" Stationary
<b>Axles</b>	(2) 22,500 lb. Oil Bath heavy duty axle with automatic slack adjusters and park brake (one axle ABS equipped)
<b>Wheel</b>	(8) 22.5" x 8.25" Hub piloted wheels, 10 on 11.25" bolt pattern
<b>Tires</b>	(8) 255/70R-22.5 tire
<b>Lighting</b>	DOT Approved, all sealed rubber mounted LED
<b>Hitch</b>	King Pin, 48" ground clearance, 2" SAE with 3/8" bolster plate
<b>Jack</b>	(2) Dual Speed Holland Landing Gear
	Reflector Tape
	Mud Flaps
<b>Finish</b>	Bead Blasted, Acid Washed, Electrostatic Powder Coat



**Manufactured by:**  
Behnke Enterprises, Inc.  
800 Ninth Ave. NW  
Farley, IA 52046  
Ph. (563)744-3246  
Fax (563)744-9066  
[www.behnkeenterprises.com](http://www.behnkeenterprises.com)